



Ride On Scrubber Drier - CRO 1185



Easy Brush Access
with ABS Brush Cover



Wet Pick Up Squeegee



Simple Maintenance



Powerful Traction System



Water inlet

CRO 1185 has great manoeuvrability, thanks to a balanced weight distribution. It is equipped with variable brush pressure which can reach upto 63kg. With its robust structure, it can deep clean efficiently, it comes with detergent control and auto stop feature. Detergent flow stops and starts upon traction pedal being activated. Extremely user friendly – it increases productivity. Low noise feature makes the machine suitable for daytime cleaning even in noise - sensitive applications. Noise level is as low as 60dBA and long hrs of battery run time. Equipped with 2 stage high suction and SUPER SILENT vacuum motor.

Advantages

- High quality vacuum seal in recovery tank: Vacuum gasket is made of elastic material, assuring the best vacuum sealing throughout the life of the machine.
- Excellent water flow into tank: Dirty water is vacuumed directly from the squeegee, runs on a curve a curve made on the hood.
- New SUPER SILENT Technology 60dBA.
- CFS (Center Flow System): Centre spray solution outlet on the brush ensures the entire use of the brush and does not waste water and detergent.
- 3 X more productivity than walk-behind scrubbers. Saves on Manpower.
- Compact smart design, User Friendly.
- Super Silent – Eco Mode system.
- Large tanks: 70L, perfect suction performance.
- The intelligent water sensor system, ensure maximum protection for brushes and vacuum system
- Rear-wheel drive, climbing capacity reaches to 20% while turning radius 0.8 Meter.
- Chemical Dosage System with 3 dilutions.
- Brush pressure Boost.
- 3 cleaning modes.
- Connect and disconnect brushes automatically, Electronic brush and squeegee up/down, Easy to maintain.



HOURLY PERFORMANCE

5950 M²/H

Cleaned Track Width	Squeegee Width	Number of Brushes	Brush Diameter	Max Brush Pressure	Brush Speed	Brush Motor Power	Drive Motor Rated Power	Maximum Speed	VAC Motor	Solution Tank
850 mm	1120 mm	2	435 mm	63 kg	140 rpm	500 W	600 W	6 km/h	375 W	110 L

Recovery Tank	Wheel Diameter	Net Weight Without Batteries	Number of Batteries	Series Battery Capacity	Single Battery Capacity	Single Battery Weight	Power Supply Voltage	Battery Compartment Size	Machine Size	Dimensions of Packaging
110 L	Front-250 Rear: 300 mm	233 Kg	4	24 V	6 v-225 Ah	33 Kg	24 V	520x380x390 mm	1540x897x1287 mm	1560x980x1460 mm