

Ride-on Scrubber Drier - CRO 1185



Easy Brush Access with ABS Brush Cover



Wet Pick Up Squeegy



Simple Maintenance




Powerful Traction System

CRO 1185 has great manoeuvrability, thanks to a balanced weight distribution. It is equipped with variable brush pressure which can reach up to 63kg. With its robust structure, it can deep clean efficiently. It comes with detergent control and auto stop feature. Detergent flow stops and starts upon traction pedal being activated. Low noise feature makes the machine suitable for daytime cleaning even in noise-sensitive applications. Noise level is as low as 60dBA. Equipped with 2 stage high suction and SUPER SILENT vacuum motor.

Advantages:

- High-quality vacuum seal in recovery tank: Vacuum gasket is made of elastic material, assuring the best vacuum sealing throughout the life of the machine.
- Excellent water flow into the tank: Dirty water is vacuumed directly from the squeegee, runs on a curve made on the hood.
- New SUPER SILENT Technology 60dBA.
- CFS (Center Flow System): Centre spray solution outlet on the brush ensures the entire use of the brush and does not waste water and detergent.
- 3 X more productivity than walk-behind scrubbers. Saves on Manpower.
- · Compact smart design, User Friendly.
- Super Silent Eco Mode system.
- Large tanks: 110 L, perfect suction performance.
- The intelligent water sensor system, ensure maximum protection for brushes and vacuum system.



- · Chemical Dosage System with 3 dilutions.
- Brush pressure Boost.
- 3 cleaning modes.
- Connect and disconnect brushes automatically, Electronic brush and squeegee up/down, Easy to maintain.

Technical Specification HOURLY PERFORMANCE



	Model No.	Cleaned Track Width		gee Numb h Brusl			Max Brush Pressure			or Drive Moto Rated Powe		VAC Motor		r Dirty Water Capacity	
	CRO 1185	850 mm	1120 m	nm 2	,	435 mm	63 Kg	140 RPI	M 500 W	600 W	7.5 km/h	375 W	110 L	110 L	
		Net We Without Ba	•				Single Battery S Capacity		ingle Battery Weight		Battery Compartmer		Machine Size	Dimensions (LxWxH)	
Front: 250 Rear: 300 mm		233 Kg		4	24 V		6 V-225 Ah		33 Kg	24 V	520 x 38 x 390 m		1540 x 897 x 1287 mm	1560 x 980 x 1460 mm	

