

Ride-on Scrubber Drier - CRO 1185 PRO



Easy Brush Access with ABS Brush Cover



Wet Pick Up Squeegy



Simple Maintenance



Powerful Traction System

CRO 1185 PRO has great manoeuvrability, thanks to a balanced weight distribution. It is equipped with variable brush pressure which can reach up to 63kg. With its robust structure, it can deep clean efficiently. It comes with detergent control and auto stop feature. Detergent flow stops and starts upon traction pedal being activated. Low noise feature makes the machine suitable for daytime cleaning even in noise-sensitive applications. Noise level is as low as 60dBA. Equipped with 2 stage high suction and SUPER SILENT vacuum motor.

Advantages:

- High-quality vacuum seal in recovery tank: Vacuum gasket is made of elastic material, assuring the best vacuum sealing throughout the life of the machine.
- Excellent water flow into the tank: Dirty water is vacuumed directly from the squeegee, runs on a curve made on the hood.
- New SUPER SILENT Technology 60dBA.
- CFS (Center Flow System): Centre spray solution outlet on the brush ensures the entire use of the brush and does not waste water and detergent.
- 3 X more productivity than walk-behind scrubbers. Saves on Manpower.
- Compact smart design, User Friendly.
- Super Silent Eco Mode system.
- Large tanks: 110 L, perfect suction performance.
- The intelligent water sensor system, ensure maximum protection for brushes and vacuum system.
- Rear-wheel drive, climbing capacity reaches to 20% while turning radius 0.8 Meter.
- · Chemical Dosage System with 3 dilutions.
- Brush pressure Boost.
- 3 cleaning modes.
- Connect and disconnect brushes automatically, Electronic brush and squeegee up/down, Easy to maintain.

Technical Specification

HOURLY PERFORMANCE



| Model No. | Cleaned Track Width | | | er of Brush hes Width | Max Brush Pressure | | Brush Mot Power | or Drive Moto Rated Powe | | VAC Motor | | Dirty Water Capacity |
|----------------------------|------------------------|--------|------|---------------------------|-----------------------|---------|-----------------------|-----------------------------|--------------------------------|--------------|--------------------|-------------------------|
| CRO 1185 PRO | 850 mm | 1120 n | nm 2 | 435 mm | 63 Kg | 140 RPM | 500 W | 600 W | 6 km/h | 375 W | 110 L | 110 L |
| Wheel Diameter | Net We Without Ba | | | Series Batter Capacity | Single Ba Capaci | | gle Battery Weight | Power Supply Voltage | Approx Run Time on Full Charge | | | Dimensions (LxWxH) |
| Front: 250 Rear: 300 mm | 233 Kg | | 4 | 24 V | 6 V-225 Ah | | 33 Kg | 24 V | 3-4 Hours | 1 . | 20 x 380 390 mm | 1560 x 980 x 1460 mm |